




**FROM PELLET TO PART**  
YOUR PARTNER  
FOR PRODUCTIVITY  
AND SUSTAINABILITY



**SLIDE®**

PREMIUM HIGH-HEAT PFAS-FREE GREASE

## PROTECT ALL MOVING MOLD COMPONENTS FROM FRICTION, WEAR AND CORROSION!

**Slide UltraHeat Grease** delivers exceptional thermal and mechanical stability, maintaining its integrity even during rapid temperature fluctuations. Tested to withstand consistent temperatures exceeding 650°F (343°C) without melting or discoloring, it is the premier choice for high-heat mold components. This NSF H1-registered lubricant is safe for incidental food contact and contains no PFAS, PFOA, or PFOS.

ITEM NO.	DESCRIPTION
48300T	14OZ CARTRIDGE TUBE

- High Operating Temperature Level 650°F (343°C)
- PFAS- Free Formula
- Ceramic-Based Lubricant
- Contains No PTFE or Silicone
- NLGI 2 Grease
- NSF Category H1 Lubricant



**SLIDE®**

**Withstands 650°F (343°C)+ without melting or discoloring**

**DME Company LLC**  
42827 Irwin Dr.,  
Harrison Twp., MI 48045  
**800-626-6653 toll-free tel**  
**www.dme.net web**  
DME@DME.net e-mail

**DME Canada**  
41 Todd Road,  
Georgetown, Ontario  
Canada L7G 4R8  
**800-387-6600 toll-free tel**  
DME\_Canada@DME.net e-mail

**eSTORE**  
store.dme.net

